



SAFETY DATA SHEET
POLYURETHANE EXPANSION JOINT SYSTEM- PART A

Page 1

Issued: 18/06/01

Revision No: 3

P.R. Epoxy Systems Ltd
Unit D2, The Court
Kestrel Road
TRAFFORD PARK
Manchester
M17 1SF
Tel: 0161 872 7618
Fax: 0161 876 4597

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: POLYURETHANE EXPANSION JOINT SYSTEM- PART A

Use / description of product: No significant hazard.

2. COMPOSITION / INFORMATION ON INGREDIENTS

Contains: Mixture of Branched Polyols fillers and extenders not classified under CHIP as a hazard to health.

3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

4. FIRST AID MEASURES (SYMPTOMS)

4. FIRST AID MEASURES (ACTION)

Skin contact: Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Water. Water spray. Dry chemical powder.

Protection of fire-fighters: Normal equipment

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Absorb into dry earth or sand.

7. HANDLING AND STORAGE

Handling requirements: Avoid prolonged contact with the product.

Storage conditions: Store in cool, well ventilated area. Avoid incompatible materials and conditions - see section 10 of SDS.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hand protection: Protective gloves.

Eye protection: Safety goggles.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

[cont...]

9. PHYSICAL AND CHEMICAL PROPERTIES**State:** Liquid**Odour:** Sweet-smelling**Solubility in water:** Insoluble**Boiling point/range°C:** >2000°C**Flash point°C:** >200°C-open cup**Autoflammability°C:** >200°C**Relative density:** 1.5**pH:** N/A**10. STABILITY AND REACTIVITY****Conditions to avoid:** Will decompose on prolonged storage at temperatures of 150°C or above.**Materials to avoid:** Strong oxidising agents.**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide and carbon monoxide.**11. TOXICOLOGICAL INFORMATION****12. ECOLOGICAL INFORMATION****13. DISPOSAL CONSIDERATIONS****Waste disposal:** Arrange for collection by specialised disposal company.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****IMDG / IMO****IATA / ICAO****15. REGULATORY INFORMATION****Hazard symbols:** No significant hazard.**Safety phrases:** S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28: After contact with skin, wash immediately with plenty of soap and water.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.**16. ADDITIONAL INFORMATION****Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.